

HAMILTON MATERIALS

The Professional's Choice for Drywall Finishing Products



		CHEMICAL SET COMPOUNDS							AIR DRYING JOINT COMPOUNDS								
		PATCHING			BASE COATS				TAPING		ALL PURPOSE				TOPPING		
		FASTSET 5	FASTSET 20	FASTSET 40	SMOOTHSET 40	SMOOTHSET 90	SMOOTHSET 90 LITE	SMOOTHSET 180 LITE	BLUE DOT	BLUE DOT LITE	RED DOT	TNT LITE	HI LITE	SUPERLITE	GREEN DOT	GREEN DOT LITE	BLACK DOT
APPLICATION	BASE COAT	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT	GOOD	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT	FAIR	LOW	LOW	-	-	-
	SECOND COAT				GOOD	GOOD	GOOD	GOOD	-	-	GOOD	EXCELLENT	EXCELLENT	GOOD	GOOD	GOOD	GOOD
	TOP COAT				-	-	-	-	-	FAIR	FAIR	EXCELLENT	EXCELLENT	GOOD	EXCELLENT	EXCELLENT	EXCELLENT
	SKIMMING				-	-	-	-	-	-	FAIR	GOOD	GOOD	GOOD	EXCELLENT	EXCELLENT	EXCELLENT
	SHRINKAGE				-	-	-	-	HIGH	MEDIUM	HIGH	VERY LOW	LOW	LOW	VERY LOW	LOWEST	LOW
	COMPOUND TYPE	CHEM-SET	AIR DRYING	AIR DRYING	DRYING	AIR DRYING	AIR DRYING	AIR DRYING	AIR DRYING	AIR DRYING	AIR DRYING						
	SANDING	EASY	EASY	EASY	FAIR	FAIR	GOOD	GOOD	DIFFICULT	FAIR	DIFFICULT	EASY	GOOD	EASIEST	EASY	EASIER	EASIEST
	WORKING TIME	5 - 7 MIN	20 - 25 MIN	40 - 48 MIN	40 - 48 MIN	85 - 100 MIN	85 - 100 MIN	170 - 185 MIN	-	-	-	-	-	-	-	-	-
	SET TIME	7 - 9 MIN	25 - 30 MIN	60 - 60 MIN	50 - 60 MIN	100 - 125 MIN	100 - 125 MIN	190 - 205 MIN	-	-	-	-	-	-	-	-	-
	PACKAGING & SIZE	8.2KG	8.2KG	8.2KG	20KG BAG	20KG BAG	18KG BAG	18KG BAG	13.6L CARTON	13.6L CARTON	18L PAIL / 13.6L CARTON	15L PAIL / 13.6L CARTON	18L PAIL / 13.6L CARTON	13.6L CARTON	18L PAIL / 13.6L CARTON	13.6L CARTON	13.6L CARTON
	BENEFITS	<ul style="list-style-type: none"> • Excellent bond • Smooth finish • Harder finish 	<ul style="list-style-type: none"> • Excellent bond • Smooth finish • Harder finish 	<ul style="list-style-type: none"> • Excellent bond • Smooth finish • Harder finish 	<ul style="list-style-type: none"> • Excellent bond • Smooth finish • Harder finish 	<ul style="list-style-type: none"> • Excellent bond • Smooth finish • Harder finish 	<ul style="list-style-type: none"> • Excellent bond • Smooth finish • Harder finish 	<ul style="list-style-type: none"> • Excellent bond • Smooth finish • Harder finish 	<ul style="list-style-type: none"> • Super Slick • Great open time • Great bond 	<ul style="list-style-type: none"> • Easy handling for increased productivity • Great open time • Great bond 	<ul style="list-style-type: none"> • Use for taping, topping and texturing • Excellent bond and low shrinkage • Excellent for all applications 	<ul style="list-style-type: none"> • Less weight increases ease of finishing and handling • Low shrinkage • One mud system decreases waste 	<ul style="list-style-type: none"> • Less weight increases ease of finishing and handling • Low shrinkage • One mud system decreases waste 	<ul style="list-style-type: none"> • 40% lighter than conventional joint compounds • Easy handling for increased productivity • Excellent workability, easy sanding and low shrinkage 	<ul style="list-style-type: none"> • Very low shrinkage • For second and finish coats • Easy sanding • Can be used a texture spray 	<ul style="list-style-type: none"> • Easy handling for increased productivity • Excellent workability • Easy sanding & low shrinkage 	<ul style="list-style-type: none"> • For second and finish coats • Low shrinkage • Easiest sanding • Tinted

***All Joint compounds meet ASTM C-475

For more information call Manners Building Products **0800 6266377** or visit www.hamiltondrywall.co.nz